

ダブルツイスト撚戻送線機(型式: BP8-7B)



特徴

- ・LCD用極細線同軸ケーブル、医療機器電線用導体、極細線の同心・集合撚りの生産に最適です。
- ・ダブルツイストバンチャーとの連動で、断線率の軽減化ができ生産性が上がります。

主仕様

■型式	BP8-7B
■回転数	max 4,000rpm/8,000TPM
■素線径	0.025 ~ 0.08mm
■軸受給油方式	グリス密閉式軸受(メンテナンス不要)
■撚戻率	0 ~ 120% (0.1%刻み)
■送線ポピン	NR-80 鋸径 max 80mm 外幅 max 80mm
■送線張力	0.05~0.3N (5~30g)
■送線張力制御	ダンサー制御
■寸法/重量	900mm(W) × 910mm(D) × 1,700mm(H) / 690kg

Double Back Twist Pay-Off (Model: BP8-7B)



Features

- Appropriate to production of conductor strand for micro coaxial cable for LCD and medical equipment wire and also concentric and aggregated strand for super fine wire.
- The rate of wire break is decreased in conjunction with a double twist buncher and leads to better productivity.

Main Specifications

■ Model	BP8-7B
■ Rotation speed	max 4,000rpm/8,000TPM
■ Single wire	0.025 ~ 0.08mm
■ Lubrication system for main baring	Sealed type for main shaft (Maintenance free)
■ Back twist rate	0 ~ 120% (By 0.1%)
■ Pay-off bobin	NR-80 Flange max 80mm O.A.W. max 80mm
■ Pay-off tension	0.05~0.3N (5~30g)
■ Pay-off tension control	Mechanical dancer control
■ Dimensions/Weight	900mm(W) × 910mm(D) × 1,700mm(H) / 690kg